

FREESTYLE PHOTOGRAPHIC SUPPLIES PREMIUM ARISTA B&W CHROMO ACTIVATOR

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Distributor: Freestyle Photographic Supplies Product Name: **B&W CROMO ACTIVATOR**

5124 Sunset Blvd., Hollywood, CA 90027

Product Number: 10945 Date Prepared: 02/18/2009

Customer Information Phone Number: 1-800-292-6137

CHEMTREC®: 24 Hour Emergency Transport Phone Number: 1-800-424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS	OHSA PEL	ACGIH TLV	Weight %
POTASSIUM HYDROXIDE	1310-58-3	N.E.	2mg/m³ CEILING	5-10
SODIUM SULFITE	7757-83-7	N.E.	N.E.	5-10

3. HAZARDOUS IDENTIFICATION

POTENTIAL HEALTH EFFECTS

Emergency Overview: **DANGER! CORROSIVE** to skin, eyes, and all tissues.

Eye Contact: Corrosive to eyes. May cause irritation or permanent damage to tissue.

Inhalation: Expected to be a low hazard for usual industrial or commercial handling by trained personnel. Inhalation of the mist could cause respiratory irritation. If heated, or in contact with strong acids, sulfites may liberate sulfur dioxide gas.

Ingestion: May be harmful if swallowed. Alkaline nature of solution may cause irritation or corrosion to digestive tract, including perforation of mucous membranes of the mouth, throat, esophagus and stomach.

Skin Contact: Substance is corrosive. Can cause severe skin burns. Some asthmatics and sulfitesensitive individuals may experience a reaction.

Signs And Symptoms Of Exposure: Eye pain, respiratory irritation, difficulty breathing, abdominal pain, skin blistering, mucus membrane irritation, coughing.

4. FIRST AID MEASURES

Eye Contact: Immediately flush eyes with water for at least 15 minutes. Get immediate medical attention.

Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention immediately.

Ingestion: If swallowed, DO NOT induce vomiting. Give large quantities of water. Call a physician or poison control center.

Skin Contact: Wash with soap and water. Get medical attention if irritation develops or persists. Aggravated Medical Conditions: Individuals who are under the care of a physician or have chronic ailments, should consult a physician before using this product. Some asthmatics and sulfite-sensitive individuals may experience wheezing, chest tightness, stomach upset, hives, diarrhea.

MATERIAL SAFETY DATA SHEET



Supplemental Health Information: None of the components in this product is listed by IARC, NTP, or OSHA as carcinogen.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES

Flash Point: Nonflammable Flash Point Method: Not applicable Auto ignition: Not applicable

LEL: Not applicable UEL: Not applicable

Extinguishing Media: Use alcohol foam, carbon dioxide, or water spray when fighting fires involving

this material.

Special Fire-Fighting Procedures: Firefighters should wear proper protective equipment and selfcontained breathing apparatus with full face piece in positive pressure mode. Move containers from fire area if it can be done without risk. Use water to keep fire-exposed containers cool.

Unusual Fire And Explosion Hazards: None known.

Combustion Products: Carbon dioxide, carbon monoxide, oxides of sulfur.

6. ACCIDENTAL RELEASE MEASURES

Steps To Be Taken In Case Material Is Spilled Or Released: Review fire and explosion hazards and safety precautions before proceeding with cleanup. Use appropriate personal protective equipment. Avoid contact with skin and eyes. Stop the spillage. Dike the spill. Prevent liquid from entering sewers, waterways or low areas. Neutralize with a weak acid solution. Avoid splashing or misting which could increase health hazards. Absorb spillage in inert material. Soak up with sawdust, sand, or other absorbent material. Remove non-usable solid material and/or contaminated soil for disposal in an approved and permitted landfill. Discharge to sewer requires approval of permitting authority and may require pre-treatment. Contaminated surfaces should be cleaned using water.

7. HANDLING AND STORAGE

Precautions To Be Taken In Handling And Storage: Store in a cool, dry, well ventilated area. Keep containers closed. Do not store with incompatible materials. Do not store or consume food, drink, or tobacco where they may become contaminated with this material.

Other Precautions: All labeled precautions must be observed when handling, storing and transporting empty containers due to product residues. Do not reuse containers. Triple rinse before disposal. Dispose of in a licensed facility. Recommended crushing or other means to prevent re-use.

8. EXPOSURE CONTROL / PERSONAL PROTECTION

PERSONAL PROTECTIVE EQUIPMENT

Respiratory Protection: Use of respiratory protection is generally not required. However, if use conditions generate vapors or fumes, use a NIOSH approved acid gas respirator.

Ventilation: Provide exhaust ventilation sufficient to keep the airborne concentration of this product below its exposure limits. Good ventilation (typically 10 air changes per hour) should be used.

Protective Gloves: Rubber or neoprene waterproof gloves are recommended.

Eye Protection: Safety glasses with side shields (or goggles)/face shield.

Other Protective Clothing or Equipment: Rubber or plastic apron.

Work/Hygienic Practices: Use good personal hygiene when handling this product. Wash hands after use, before smoking, or using the toilet.

MATERIAL SAFETY DATA SHEET



Engineering Controls: Facilities storing or utilizing this material should be equipped with an eyewash

facility and a safety shower.

Exposure Guidelines: See Section 2.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance And Odor: Clear, colorless, and odorless

Solubility In Water: Complete

Boiling Point: >212° F Vapor Pressure: N.E. Specific Gravity: 1.116

Melting Point: Not applicable

Freezing Point: N.E. Evaporation Rate: <1 Vapor Density: N.E. Percent Volatile: 86.40 Ph: Highly alkaline 14

Molecular Weight: Not applicable

Pounds Per Gallon: 9.30

V.O.C. = 0

10. STABILITY AND REACTIVITY

Stability: Stable

Conditions To Avoid: None

Incompatibility: Strong acids, alkalis, and oxidizers. Common metals other than stainless steel.

Hazardous Decomposition Or By Products: Carbon dioxide and carbon monoxide and oxides of sulfur.

Hazardous Polymerization: Will Not Occur

Conditions To Avoid: None known.

11. TOXICOLOGICAL INFORMATION

12. ECOLOGICAL INFORMATION

13. DISPOSAL CONSIDERATIONS

The preferred options for disposal are to send to licensed reclaimers, or to permitted incinerators. Any disposal practice must be in compliance with federal, state, and local regulations. Do not dump into sewers, ground, or any body of water.

14. TRANSPORT INFORMATION

DOT Class: CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Contains Potassium Hydroxide)

Hazard Class: 8 UN No.: 3266 Packing Group: II Guide No: 154

Limited Quantity Exception may apply to this product, for "inner packagings not over 1.0L (0.3 gal) for liquids and 1.0 kg (2.2 lb) for solids". 173.154 (b) (1). Each package must conform to the packaging

MATERIAL SAFETY DATA SHEET



requirements of Subpart B of Part 173 and may not exceed 30 kg (66 lb) gross weight. For further information consult the 49 CFR.

DOT Class: CONSUMER COMMODITY, ORM-D

Hazard Class: NOT APPLICABLE

UN No.: NOT APPLICABLE

Packing Group: NOT APPLICABLE Guide No: NOT APPLICABLE Ship Name: NOT APPLICABLE

15. REGULATORY INFORMATION

TSCA: All ingredients in this finished product are listed on the EPA TSCA INVENTORY.

SARA TITLE III: NONE CALIF. PROP. 65: NONE

CARCINOGENICITY: NONE OF THE COMPONENTS IN THIS CHEMICAL IS LISTED BY IARC,

NTP, OR OSHA AS A CARCINOGEN.

SCAQMD Rule 443.1

Photochemically Reactive: No

Maximum Grams of VOC per Liter: 0g/L

Vapor Pressure: N.E. mm Hg@ 20 Degrees C

16. OTHER INFORMATION (HMIS)

Health: 3

Flammability: 0 Reactivity: 0 Protective: D

OTHER ADDITIONAL INFORMATION: The information and recommendations contained herein are based on data believed to be correct. However, no guarantee or warranty of any kind expressed or implied is made with respect to the information contained herein.