

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
000000014901/Version: 1.0
Print Date: 10/23/2006
Page: 1/6



1. Identification of the substance/preparation and of the company/undertaking

Product name: KODAK PROFESSIONAL First Developer Replenisher, Process E-6 and Process E-6AR, Working Solution

Product code: 8008401 - Working Solution

Manufacturer: EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York, 14650

Supplier: EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York, 14650

For Emergency Health, Safety & Environmental Information, call (585) 722-5151 (USA)

For other information or to request an MSDS, call (800) 242-2424.

Synonyms: None.

2. Hazards identification

CONTAINS: Potassium hydroquinone monosulphonate (21799-87-1), Potassium sulphite (10117-38-1)

WARNING!

MAY BE HARMFUL IF SWALLOWED.

MAY LIBERATE SULFUR DIOXIDE

CAUSES EYE IRRITATION

MAY CAUSE ALLERGIC SKIN REACTION

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE DRYING, CRACKING, OR IRRITATION

LOW PHYSICAL HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING

HMIS II Hazard Ratings:

Health - 2, Flammability - 0, Reactivity (Stability) - 0

NFPA Hazard Ratings:

Health - 2, Flammability - 0, Instability - 0

NOTE: HMIS II and NFPA hazard indexes involve data review and interpretation that may vary among companies. They are intended only for rapid, general identification of the magnitude of the potential hazards. An asterisk (*), in the HMIS II health field, designates potential chronic or target organ hazards. To adequately address safe handling, ALL information in this MSDS must be considered.

3. Composition/information on ingredients

Weight %	Components (CAS-No.)
90 - 95	Water (7732-18-5)
1 - 5	Potassium sulphite (10117-38-1)
1 - 5	Potassium hydroquinone monosulphonate (21799-87-1)
1 - 5	Potassium carbonate (584-08-7)

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
000000014901/Version: 1.0
Print Date: 10/23/2006
Page: 2/6

< 1

Sodium carbonate (497-19-8)

4. First aid measures

Inhalation: If symptomatic, move to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Eyes: Immediately flush eyes for at least 15 minutes. Get medical attention.

Skin: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if symptoms occur. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes.

Ingestion: Drink 1-2 glasses of water. Seek medical attention. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: None (noncombustible), (see also Hazardous Decomposition Products section).

Unusual Fire and Explosion Hazards: None.

6. Accidental release measures

Methods for cleaning up: Flush into sewer with plenty of water. Otherwise, absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

7. Handling and storage

Personal precautions: Avoid prolonged or repeated breathing of mist or vapour. Avoid contact with eyes, skin, and clothing. Ensure adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: No special technical protective measures required.

Storage: Keep container tightly closed. Keep away from incompatible substances (see Incompatibility section.)

8. Exposure controls / personal protection

Occupational exposure controls

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
000000014901/Version: 1.0
Print Date: 10/23/2006
Page: 3/6

Chemical Name	Regulatory List	Value Type	Value
Sulphur dioxide	ACGIH	Time Weighted Average (TWA):	2 ppm
	ACGIH	Short Term Exposure Limit (STEL):	5 ppm
	OSHA Z1	PEL:	5 ppm 13 mg/m3

Ventilation: Good general ventilation should be used. Ventilation should be sufficient so that applicable occupational exposure limits are not exceeded. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances.

Respiratory protection: If engineering controls do not maintain airborne concentrations to an acceptable level, an approved respirator must be worn. Respirator type: Acid gas. If respirators are used, a program should be instituted to assure compliance with OSHA Standard 29 CFR 1910.134.

Eye protection: Wear safety glasses with side shields (or goggles).

Skin and body protection: Wear impervious gloves and protective clothing appropriate for the risk of exposure.

Recommended Decontamination Facilities: Safety shower, eye wash, washing facilities as appropriate to condition of use.

9. Physical and Chemical Properties

Physical form: liquid

Colour: light amber

Odour: odourless

Specific gravity: No data available

Vapour pressure (at 20.0 °C (68.0 °F)) : 24 mbar (18.0 mm Hg)

Vapour density: 0.6

Volatile fraction by weight: 90 - 95 %

Boiling point/range: 100.0 °C (212.0 °F)

Water solubility: complete

pH: No data available

Flash point: none, noncombustible liquid

10. Stability and reactivity

Stability: Stable.

Incompatibility: Acids. Contact with strong acids liberates sulphur dioxide.

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
000000014901/Version: 1.0
Print Date: 10/23/2006
Page: 4/6

Hazardous decomposition products: Carbon oxides, sulphur oxides.

Hazardous Polymerization: Hazardous polymerization does not occur.

11. Toxicological information

Effects of Exposure

Inhalation: Expected to be a low hazard for recommended handling. In contact with strong acids or if heated, sulphites may liberate sulphur dioxide gas. Sulphur dioxide gas is irritating to the respiratory tract. Some asthmatics or hypersensitive individuals may experience difficult breathing.

Eyes: Causes eye irritation.

Skin: May cause allergic skin reaction.

Ingestion: May be harmful if swallowed. Some asthmatics or sulfite-sensitive individuals may experience wheezing, chest tightness, stomach upset, hives, faintness, weakness and diarrhea.

12. Ecological information

The following properties are ESTIMATED from the components of the preparations.

Potential Toxicity:

Fish LC50: > 100 mg/l

Daphnid EC50: > 100 mg/l

Algal IC50: > 100 mg/l

Waste treatment organisms EC50: > 100 mg/l

Organics Readily Degradable: Yes

Potential Bioaccumulation: $\log Pow < 1$

COD (approximate): 21 g/l

BOD (approximate): 12 g/l

13. Disposal considerations

Discharge, treatment, or disposal may be subject to federal, state, commonwealth, provincial, or local laws. Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
000000014901/Version: 1.0
Print Date: 10/23/2006
Page: 5/6

For transportation information regarding this product call the Kodak Worldwide Transportation Hazmat Hot Line: (585) 722-2400 between 8 a.m. and 5 p.m. (Eastern Standard Time), Monday through Friday. In Canada: General Shipping Information, call: (416) 766-8233.

15. Regulatory information

U.S. California Prop. 65: none

Carcinogenicity Classification (components present at 0.1% or more):

International Agency for Research on Cancer (IARC): Potassium sulphite: 3 (not classifiable as to carcinogenicity to humans), Sulphur dioxide: 3 (Classification not possible from current data.)
American Conference of Governmental Industrial Hygienists (ACGIH): Sulphur dioxide: Group A4 (Not classifiable as a human carcinogen.)
U.S. National Toxicology Program (NTP): none
U.S. Occupational Safety and Health Administration (OSHA): none

Chemical(s) subject to the reporting requirements of U.S. Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372: none

16. Other information

US/Canadian Label Statements:

CONTAINS: Potassium hydroquinone monosulphonate (21799-87-1), Potassium sulphite (10117-38-1)

WARNING!

MAY BE HARMFUL IF SWALLOWED.

MAY LIBERATE SULFUR DIOXIDE

CAUSES EYE IRRITATION

MAY CAUSE ALLERGIC SKIN REACTION

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE DRYING, CRACKING, OR IRRITATION

LOW PHYSICAL HAZARD FOR USUAL INDUSTRIAL OR COMMERCIAL HANDLING

Avoid prolonged or repeated breathing of mist or vapour.

Avoid contact with eyes, skin, and clothing.

Ensure adequate ventilation.

Wash thoroughly after handling.

FIRST AID: If swallowed, drink 1-2 glasses of water. Seek medical attention. Never give anything by mouth to an unconscious person. In case of eye contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention. In case of skin contact, immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if symptoms occur. Destroy or thoroughly clean contaminated shoes.

Keep out of reach of children.

For additional information, see Material Safety Data Sheet (MSDS) for this material.

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
000000014901/Version: 1.0
Print Date: 10/23/2006
Page: 6/6

Since emptied containers retain product residue, follow label warnings even after container is emptied.

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. The information relating to the working solution is for guidance purposes only, and is based on correct mixing and use of the product according to instructions.

R-1, S-2, F-0, C-0

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
Z17000000389/Version: 1.0
Print Date: 10/23/2006
Page: 1/6



1. Identification of the substance/preparation and of the company/undertaking

Product name: KODAK PROFESSIONAL First Developer Replenisher, Process E-6 and Process E-6AR

Product code: 8008401

Manufacturer: EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York, 14650

Supplier: EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York, 14650

For Emergency Health, Safety & Environmental Information, call (585) 722-5151 (USA)

For other information or to request an MSDS, call (800) 242-2424.

Synonyms: PCD 6214

2. Hazards identification

CONTAINS: Potassium sulphite (10117-38-1), 4-hydroxymethyl-4-methyl-1-phenyl-3-pyrazolidinone (13047-13-7), Potassium hydroquinone monosulphonate (21799-87-1)

WARNING!

MAY BE HARMFUL IF SWALLOWED.

MAY LIBERATE SULFUR DIOXIDE

CAUSES EYE IRRITATION

MAY CAUSE ALLERGIC SKIN REACTION

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE DRYING, CRACKING, OR IRRITATION

HMIS II Hazard Ratings:

Health - 2, Flammability - 0, Reactivity (Stability) - 0

NFPA Hazard Ratings:

Health - 2, Flammability - 0, Instability - 0

NOTE: HMIS II and NFPA hazard indexes involve data review and interpretation that may vary among companies. They are intended only for rapid, general identification of the magnitude of the potential hazards. An asterisk (*), in the HMIS II health field, designates potential chronic or target organ hazards. To adequately address safe handling, ALL information in this MSDS must be considered.

3. Composition/information on ingredients

Weight %	Components (CAS-No.)
65 - 70	Water (7732-18-5)
10 - 15	Potassium sulphite (10117-38-1)
5 - 10	Potassium hydroquinone monosulphonate (21799-87-1)
5 - 10	Potassium carbonate (584-08-7)

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
Z17000000389/Version: 1.0
Print Date: 10/23/2006
Page: 2/6

1 - 5 Sodium carbonate (497-19-8)
< 1 4-hydroxymethyl-4-methyl-1-phenyl-3-pyrazolidinone (13047-13-7)

4. First aid measures

Inhalation: If symptomatic, move to fresh air. Treat symptomatically. Get medical attention if symptoms occur.

Eyes: Immediately flush eyes for at least 15 minutes. Get medical attention.

Skin: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention if symptoms occur. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes.

Ingestion: Drink 1-2 glasses of water. Seek medical attention. Never give anything by mouth to an unconscious person.

5. Fire-fighting measures

Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: None (noncombustible), (see also Hazardous Decomposition Products section).

Unusual Fire and Explosion Hazards: None.

6. Accidental release measures

Methods for cleaning up: Flush into sewer with plenty of water. Otherwise, absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

7. Handling and storage

Personal precautions: Avoid breathing mist or vapour at concentrations greater than the exposure limits. Avoid contact with eyes, skin, and clothing. Ensure adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: No special technical protective measures required.

Storage: Keep container tightly closed. Keep away from incompatible substances (see Incompatibility section.)

8. Exposure controls / personal protection

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
Z17000000389/Version: 1.0
Print Date: 10/23/2006
Page: 3/6

Occupational exposure controls

Chemical Name	Regulatory List	Value Type	Value
Sulphur dioxide	ACGIH	Time Weighted Average (TWA):	2 ppm
	ACGIH	Short Term Exposure Limit (STEL):	5 ppm
	OSHA Z1	PEL:	5 ppm 13 mg/m3

Ventilation: Good general ventilation should be used. Ventilation should be sufficient so that applicable occupational exposure limits are not exceeded. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances.

Respiratory protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits, an approved respirator must be worn. Respirator type: Acid gas. If respirators are used, a program should be instituted to assure compliance with OSHA Standard 29 CFR 1910.134.

Eye protection: Wear safety glasses with side shields (or goggles).

Skin and body protection: Wear impervious gloves and protective clothing appropriate for the risk of exposure.

Recommended Decontamination Facilities: Safety shower, eye wash, washing facilities as appropriate to condition of use.

9. Physical and Chemical Properties

Physical form: liquid

Colour: amber

Odour: sweet

Specific gravity: 1.28

Vapour pressure (at 20.0 °C (68.0 °F)) : 24 mbar (18.0 mm Hg)

Vapour density: 0.6

Volatile fraction by weight: 65 - 70 %

Boiling point/range: 100.0 °C (212.0 °F)

Water solubility: complete

pH: 9.9

Flash point: none, noncombustible liquid

10. Stability and reactivity

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
Z17000000389/Version: 1.0
Print Date: 10/23/2006
Page: 4/6

Stability: Stable.

Incompatibility: Acids. Contact with strong acids liberates sulphur dioxide.

Hazardous decomposition products: Carbon oxides, sulphur oxides.

Hazardous Polymerization: Hazardous polymerization does not occur.

11. Toxicological information

Effects of Exposure

Inhalation: Expected to be a low hazard for recommended handling. In contact with strong acids or if heated, sulphites may liberate sulphur dioxide gas. Sulphur dioxide gas is irritating to the respiratory tract. Some asthmatics or hypersensitive individuals may experience difficult breathing.

Eyes: Causes eye irritation.

Skin: May cause allergic skin reaction. Prolonged or repeated skin contact may cause irritation.

Ingestion: May be harmful if swallowed. Some asthmatics or sulfite-sensitive individuals may experience wheezing, chest tightness, stomach upset, hives, faintness, weakness and diarrhea.

12. Ecological information

The following properties are ESTIMATED from the components of the preparations.

Potential Toxicity:

Fish LC50:	> 100 mg/l
Daphnid EC50:	10 - 100 mg/l
Algal IC50:	> 100 mg/l No data available

Waste treatment organisms EC50: > 100 mg/l

Organics Readily Degradable: Readily biodegradable

Potential Bioaccumulation: $\log Pow < 1$

COD (approximate): 130 g/l

BOD (approximate): 72 g/l

13. Disposal considerations

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
Z17000000389/Version: 1.0
Print Date: 10/23/2006
Page: 5/6

Discharge, treatment, or disposal may be subject to federal, state, commonwealth, provincial, or local laws. Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

Not regulated for all modes of transportation.

For transportation information regarding this product call the Kodak Worldwide Transportation Hazmat Hot Line: (585) 722-2400 between 8 a.m. and 5 p.m. (Eastern Standard Time), Monday through Friday. In Canada: General Shipping Information, call: (416) 766-8233.

15. Regulatory information

U.S. California Prop. 65: none

Carcinogenicity Classification (components present at 0.1% or more):

International Agency for Research on Cancer (IARC): Potassium sulphite: 3 (not classifiable as to carcinogenicity to humans), Sulphur dioxide: 3 (Classification not possible from current data.)

American Conference of Governmental Industrial Hygienists (ACGIH): Sulphur dioxide: Group A4 (Not classifiable as a human carcinogen.)

U.S. National Toxicology Program (NTP): none

U.S. Occupational Safety and Health Administration (OSHA): none

Chemical(s) subject to the reporting requirements of U.S. Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372: none

16. Other information

US/Canadian Label Statements:

CONTAINS: Potassium sulphite (10117-38-1), 4-hydroxymethyl-4-methyl-1-phenyl-3-pyrazolidinone (13047-13-7), Potassium hydroquinone monosulphonate (21799-87-1)

WARNING!

MAY BE HARMFUL IF SWALLOWED.

MAY LIBERATE SULFUR DIOXIDE

CAUSES EYE IRRITATION

MAY CAUSE ALLERGIC SKIN REACTION

PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE DRYING, CRACKING, OR IRRITATION

Avoid prolonged or repeated breathing of mist or vapour.

Avoid contact with eyes, skin, and clothing.

Ensure adequate ventilation.

Wash thoroughly after handling.

FIRST AID: If swallowed, drink 1-2 glasses of water. Seek medical attention. Never give anything by mouth to an unconscious person. In case of contact, immediately flush eyes and skin with plenty of

MATERIAL SAFETY DATA SHEET

Revision Date: 08/10/2005
Z17000000389/Version: 1.0
Print Date: 10/23/2006
Page: 6/6

water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention. Wash contaminated clothing before re-use. Destroy or thoroughly clean contaminated shoes.

Keep out of reach of children.

For additional information, see Material Safety Data Sheet (MSDS) for this material.

Since emptied containers retain product residue, follow label warnings even after container is emptied.

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. The information relating to the working solution is for guidance purposes only, and is based on correct mixing and use of the product according to instructions.

R-1, S-2, F-0, C-0