

MATERIAL SAFETY DATA SHEET

Revision Date: 10/03/2006
000000007786/Version: 1.1
Print Date: 02/05/2007
Page: 1/6



1. Identification of the substance/preparation and of the company/undertaking

Product name: KODAK EKTACOLOR RA Bleach-Fix and Replenisher, Part A

Product code: 1815430 - Part A

Supplier: EASTMAN KODAK COMPANY, 343 State Street, Rochester, New York, 14650

For Emergency Health, Safety & Environmental Information, call (585) 722-5151 (USA)

For other information or to request an MSDS, call (800) 242-2424.

Synonyms: PCD 6565

Product Use: Professional colour film photographic processing solution

2. Hazards identification

CONTAINS: Ammonium thiosulphate (7783-18-8), Sodium bisulphite (7631-90-5), Ammonium bisulphite (10192-30-0), Ammonium sulphite (10196-04-0)

WARNING!

**DRIED PRODUCT RESIDUE CAN ACT AS A REDUCING AGENT.
MAY BE HARMFUL IF SWALLOWED.**

NFPA Hazard Ratings: Health - 3, Flammability - 1, Instability - 0

NOTE: NFPA 704 (2007) hazard indexes involves data review and interpretation that may vary among companies. It is intended only for rapid, general identification of the magnitude of the potential hazards. To adequately address safe handling, ALL information in this MSDS must be considered.

3. Composition/information on ingredients

Weight %	Components (CAS-No.)
50 - 55	Water (7732-18-5)
40	Ammonium thiosulphate (7783-18-8)
5 - 10	Sodium bisulphite (7631-90-5)
2	Ammonium bisulphite (10192-30-0)
2	Ammonium sulphite (10196-04-0)

4. First aid measures

Inhalation: If inhaled, move to fresh air. Get medical attention if symptoms occur.

Eyes: Any material that contacts the eye should be washed out immediately with water. Get medical attention if symptoms occur.

MATERIAL SAFETY DATA SHEET

Revision Date: 10/03/2006
000000007786/Version: 1.1
Print Date: 02/05/2007
Page: 2/6

Skin: Wash off with soap and water. Get medical attention if symptoms occur.

Ingestion: If swallowed, only induce vomiting as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

5. Fire-fighting measures

Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Flush with plenty of water.

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Fire or excessive heat may produce hazardous decomposition products.

Hazardous Combustion Products: Carbon oxides, nitrogen oxides (NOx), sulfur oxides, (see also Hazardous Decomposition Products section).

Unusual Fire and Explosion Hazards: Dried product residue can act as a reducing agent. Reacts violently with oxidizing materials. May cause spontaneous heating and ignition when absorbed on combustible, porous material (e.g. rags, paper, sawdust, cotton, clothing).

6. Accidental release measures

Methods for cleaning up: Collect in a noncombustible container for prompt disposal. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination.

For Large Spills: Flush with plenty of water.

7. Handling and storage

Personal precautions: Avoid breathing mist or vapour at concentrations greater than the exposure limits. Avoid contact with eyes, skin, and clothing. Use only with adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: Keep from contact with oxidizing materials, highly oxygenated or halogenated solvents, organic compounds containing reducible functional groups. Remove and wash contaminated clothing promptly.

Storage: Store in original container. Keep container tightly closed to prevent the loss of water. Keep away from incompatible substances (see Incompatibility section.)

8. Exposure controls / personal protection

Occupational exposure controls

Chemical Name	Regulatory List	Value Type	Value
Sodium bisulphite	ACGIH	time weighted average	5 mg/m3
Sulphur dioxide	ACGIH	time weighted average	2 ppm
	ACGIH	Short term exposure limit	5 ppm
	OSHA Z1	Permissible exposure limit	5 ppm 13 mg/m3

MATERIAL SAFETY DATA SHEET

Revision Date: 10/03/2006
000000007786/Version: 1.1
Print Date: 02/05/2007
Page: 3/6

Ventilation: Good general ventilation should be used. Ventilation should be sufficient so that applicable occupational exposure limits are not exceeded. Ventilation rates should be matched to conditions. Supplementary local exhaust ventilation, closed systems, or respiratory protection may be needed in special circumstances.

Respiratory protection: None should be needed under normal conditions of use. A respirator should be worn if hazardous decomposition products are likely to be or have been released. Respirator type: Acid gas. If respirators are used, a program should be instituted to assure compliance with applicable federal, state, commonwealth, provincial, or local laws and regulations.

Eye protection: Wear safety glasses with side shields (or goggles).

Skin and body protection: For operations where prolonged or repeated skin contact may occur, impervious gloves should be worn.

Recommended Decontamination Facilities: Safety shower, eye wash, washing facilities as appropriate to condition of use.

9. Physical and Chemical Properties

Physical form: liquid

Colour: clear

Odour: ammonia

Specific gravity: 1.28

Vapour pressure (at 20.0 °C (68.0 °F)) : 24 mbar (18.0 mm Hg)

Vapour density: 0.6

Volatile fraction by weight: 50 - 55 %

Boiling point/range: > 100.0 °C (> 212.0 °F)

Water solubility: complete

pH: 5.4

Flash point: does not flash

10. Stability and reactivity

Stability: Stable under normal conditions.

Incompatibility: Acids, Strong bases, sodium hypochlorite (bleach), Halogenated compounds, Oxidizing agents. Contact with sodium hypochlorite (bleach) may form chloramine (toxic gas). Contact with strong acids liberates sulphur dioxide. Contact with base liberates flammable material. Contact with base liberates ammonia.

MATERIAL SAFETY DATA SHEET

Revision Date: 10/03/2006
000000007786/Version: 1.1
Print Date: 02/05/2007
Page: 4/6

Hazardous decomposition products: Ammonia, chloramine, sulphur oxides.

Hazardous Polymerization: Hazardous polymerization does not occur.

11. Toxicological information

Effects of Exposure

Inhalation: Expected to be a low hazard for recommended handling. In contact with strong acids or if heated, sulphites may liberate sulphur dioxide gas. Sulphur dioxide gas is irritating to the respiratory tract. Some asthmatics or hypersensitive individuals may experience difficult breathing.

Eyes: No specific hazard known. May cause transient irritation.

Skin: This material has a low potential to cause allergic skin reactions; however, cases of human skin sensitization have been reported.

Ingestion: May be harmful if swallowed. May cause irritation of the gastrointestinal tract. Some asthmatics or sulfite-sensitive individuals may experience wheezing, chest tightness, stomach upset, hives, faintness, weakness and diarrhea.

Data for Sodium bisulphite (CAS 7631-90-5):

Acute Toxicity Data:

- Oral LD50 (rat): > 1,600 mg/kg

Data for Ammonium sulphite (CAS 10196-04-0):

Acute Toxicity Data:

- Oral LD50 (rat): 2,528 mg/kg
- Oral LD50: 1,904 mg/kg
- Inhalation LC50 (rat): > 2.46 mg/l / 6 hr
- Dermal LD50: > 1,000 mg/kg
- Skin irritation: slight

12. Ecological information

The following properties are ESTIMATED from the components of the preparations.

Potential Toxicity:

Fish LC50: > 100 mg/l

Daphnid EC50: > 100 mg/l

Algal IC50: 100 mg/l

Waste treatment organisms EC50: > 100 mg/l

MATERIAL SAFETY DATA SHEET

Revision Date: 10/03/2006
000000007786/Version: 1.1
Print Date: 02/05/2007
Page: 5/6

Organics Readily Degradable:	Readily biodegradable
Potential Bioaccumulation:	log Pow < 1
COD (approximate):	240 g/l
BOD (approximate):	200 g/l

13. Disposal considerations

Discharge, treatment, or disposal may be subject to federal, state, commonwealth, provincial, or local laws. Since emptied containers retain product residue, follow label warnings even after container is emptied.

14. Transport information

Not regulated for all modes of transportation.

For more transportation information, go to: www.kodak.com/go/ship.

15. Regulatory information

U.S. California Prop. 65: none

Carcinogenicity Classification (components present at 0.1% or more):

International Agency for Research on Cancer (IARC): Sodium bisulphite: 3 (Classification not possible from current data.), Ammonium bisulphite: 3 (not classifiable as to carcinogenicity to humans), Ammonium sulphite: 3 (not classifiable as to carcinogenicity to humans)
American Conference of Governmental Industrial Hygienists (ACGIH): Sodium bisulphite: Group A4 (Not classifiable as a human carcinogen.)
U.S. National Toxicology Program (NTP): none
U.S. Occupational Safety and Health Administration (OSHA): none

Chemical(s) subject to the reporting requirements of U.S. Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372: Ammonium sulphite (as a source of aqueous ammonia), Ammonium thiosulphate (as a source of aqueous ammonia), Ammonium bisulphite (as a source of aqueous ammonia)

16. Other information

The data below reflects current legislative requirements whereas the product in your possession may carry a different version of the label depending on the date of manufacture.

US/Canadian Label Statements:

CONTAINS: Ammonium thiosulphate (7783-18-8), Sodium bisulphite (7631-90-5), Ammonium bisulphite (10192-30-0), Ammonium sulphite (10196-04-0)

**WARNING!
DRIED PRODUCT RESIDUE CAN ACT AS A REDUCING AGENT.**

MATERIAL SAFETY DATA SHEET

Revision Date: 10/03/2006
000000007786/Version: 1.1
Print Date: 02/05/2007
Page: 6/6

MAY BE HARMFUL IF SWALLOWED.

Keep container tightly closed to prevent the loss of water.
Keep from contact with clothing and other materials. Remove and wash contaminated clothing promptly.
Avoid breathing vapour at concentrations greater than the exposure limits.
Avoid contact with eyes, skin, and clothing.
Use only with adequate ventilation.
Wash thoroughly after handling.

FIRST AID: If inhaled, move to fresh air. Get medical attention if symptoms occur. Any material that contacts the eye should be washed out immediately with water. Get medical attention if symptoms occur. Wash off with soap and water. Get medical attention if symptoms occur. If swallowed, only induce vomiting as directed by medical personnel. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately.

Keep out of reach of children.

Do not handle or use until safety precautions in Material Safety Data Sheet (MSDS) have been read and understood.

Since emptied containers retain product residue, follow label warnings even after container is emptied.

IN CASE OF FIRE: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Flush with plenty of water.

IN CASE OF SPILL: Collect in a noncombustible container for prompt disposal. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Clean surface thoroughly to remove residual contamination. For Large Spills: Flush with plenty of water.

The information contained herein is furnished without warranty of any kind. Users should consider these data only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use and disposal of these materials and the safety and health of employees and customers and the protection of the environment. The information relating to the working solution is for guidance purposes only, and is based on correct mixing and use of the product according to instructions.

R-1, S-1, F-1, C-1